

# Nature II Water Care System

## Start Up:

1. Fill spa with water through filter compartment.
2. Start spa by turning on GFCI Breaker.
3. Insert **Nature II or Jacuzzi ProClear Cartridge** into filter compartment
4. Add the following amounts of products per 250 gallons:  
1 oz. **Spa Shock Extra**, add this with the jets on for 30 minutes and the cover open.  
Wait 48 hours, add 2 oz. of **Protect Plus**.  
Wait 1 hour, add **Spa Perfect**.
6. Take 1 pint of spa water to Munie Leisure for fine tuning.

## Prior To Each Use:

1. Add 1/2 oz. of **Activate** per 250 gallons.  
Also add this amount if spa has not been used in three days.

## Weekly:

1. Using a Nature II test strip, test the pH, and Total Alkalinity levels of the spa, preferably two to three times weekly.
2. Add the following amounts of spa care products per 250 gallons of spa water.  
1 oz. of **Spa Shock Extra** with jets on for 30 minutes.  
1 oz. of **Protect Plus**.  
Wait 3 days, add 2 1/2 oz. of **Spa Perfect**.
3. If the pH is outside 7.4 - 7.6,  
adjust as needed with **pH Up or pH Down**.

## Monthly:

1. Have your water tested by Munie Leisure Center.
2. Rinse filters with water.

## Every 3 to 4 Months:

1. Chemically clean your filter(s) with **Filter and Cartridge Cleaner**.
2. Drain, clean, and refill your spa.  
Drain your spa by turning off the GFCI breaker.  
Remove drain cap from hose bib, attach hose and open drain.  
Clean your spa with **Spa Cleaner**.
3. Clean your cover with **303 Protectant**.

## Compatibility:

**Nature II** and **Jacuzzi Proclear** are not compatible with Bromine or Biguanides



# The keys to Great Water

## pH 7.4 - 7.6

Add pH adjusters directly to water with jet pump running.

To **raise** the pH if below 7.4, add 1/2 oz. per 250 gallons of pH Up, testing every 30-60 minutes.

To **lower** the pH if above 7.6, add pH Down. This also lowers Total Alkalinity.

If pH reading is	7.4 - 7.6	7.6 - 7.8	8.0 - 8.2	8.4
pH down for each 100 gallons	none	1/2 oz.	1 oz.	2 1/2 oz.

## Total Alkalinity 125 - 150 PPM

Add Alkalinity adjusters directly to water with jet pump running.

To **raise** the Total Alkalinity if below 125 PPM, add Total Alkalinity Increaser.

To **lower** the Total Alkalinity if above 150, add pH down. 1/2 oz. per 100 gallons. Be aware that this will also lower your pH.

If Total Alkalinity is	25 PPM	50 PPM	60 PPM	100 PPM
Alkalinity Increaser per 100 gallons	3 oz.	2 1/2 oz.	1 1/2oz.	3/4 oz.

### Measurements:

1/4 oz.= 1 teaspoon

3/4 oz. = 1 tablespoon

**Other tips:** If water becomes hazy, test and adjust pH and Total Alkalinity, then shock with 1 oz. of **Spa Shock Extra** per 250 gallons.

- \* Try **Spa Clarifier**, 1 oz. per 250 gallons to improve filter efficiency
- \* a small squirt of **Foam Out** will eliminate foam on the water surface.

**Filtration:** A good rule of thumb is to run your filter at least 1 hour, 3 times per day. Should water quality be less than desired, these times can be adjusted as needed.



4200 N. Illinois St., Swansea, IL 62226 ■ (618) 234-8004